



ELECTRONIC LEAK DETECTOR



ELECTRONIC LEAK DETECTOR P/N TELS3000

THIS LEAK DETECTOR IS THE WORLDS FIRST TRULY AUTOMATIC ELECTRONIC LEAK DETECTOR REQUIRING ABSOLUTELY NO OPERATION INTERVENTION DURING A LEAK SEARCH PROCESS.

CONTROLLED BY AN EXCLUSIVE POWERSHIFT™ SOFTWARE, THE LS3000 CONTINUOUSLY AND AUTOMATICALLY ADJUSTS CRITICAL SENSITIVITY RELATED FUNCTIONS PROVIDING OPTIMAL LEAK SEARCHING RESULTS UNDER ANY CONDITIONS.

FEATURES

- **THE WORLDS FIRST TRULY AUTOMATIC ELECTRONIC LEAK DETECTOR**
- **PATENTED MICROPROCESSOR CONTROLLED CIRCUITRY**
- **EXCLUSIVE POWERSHIFT™ SOFTWARE**
- **NEW STATE OF THE ART COLD CATHODE (CCD) SENSOR**
- **SUPERIOR RESISTANCE TO BACKGROUND CONTAMINANTS**
- **EXCLUSIVE TACHOMETER STYLE LED LEAK INDICATORS**
- **RUGGED, ERGONOMICALLY CORRECT HOUSING FITS COMFORTABLY IN YOUR HAND**
- **UP TO 75 HOURS OR MORE OF BATTERY LIFE WITH AUTO OFF FEATURE**
- **INCLUDES HARD CASE, SPARE CCD SENSOR AND 3 SIZE “C” ALKALINE BATTERIES**
- **DETECTS ALL CFC/HCFC/HFC REFRIGERANTS AND BLENDS**
- **TWO YEAR WARRANTY**
- **CERTIFIED TO SAE J1627**

AIR CONDITIONING PRODUCTS GROUP

AIR CONDITIONING TOOLS, EQUIPMENT & CONSUMABLES

ELECTRONIC LEAK DETECTOR ORDER FORM

SENSOR: STATE OF THE ART COLD CATHODE DISCHARGE DIODE.

TYPES OF GASES SENSITIVE TO ALL HALOGENATED REFRIGERANTS: CFC'S & HCFC'S.

SENSITIVITY: FULLY AUTOMATIC SENSITIVITY SELECTION WITH 6 VISIBLE LED RANGE INDICATORS. MAXIMUM SENSITIVITY ALLOWS DETECTION OF A 0.25oz/yr (7 g/yr) LEAK OF R134A (HFC).

LEAK INDICATION:

AUDIBLE ALARMS: TWO USER SELECTABLE AUDIBLE ALARM OPTIONS (HIGH & LOW INTENSITY ALARMS)

VISUAL ALARMS: TACHOMETER BAR GRAPH DISPLAY: EIGHT HIGH INTENSITY LED'S ARE ARRANGED IN TACHOMETER LIKE DISPLAY INDICATING LEAK INTENSITY.

GEARSHIFT DISPLAY: ARRANGED IN A GEARSHIFT PATTERN, SEVEN LED'S INDICATE THE CURRENT SENSITIVITY RANGE OF THE UNIT AND SUBSEQUENT LEAK SIZE AS FOLLOWS

GEAR _____ **LEAK SIZE**
 NEUTROL _____ NO LEAK
 1 & 2 _____ SMALL
 3 & 4 _____ MEDIUM
 5 & 6 _____ LARGE

OPERATING TEMPERATURE: 0° F to 140° F / -18° C to 60° C

DIMENSIONS: Instrument (LxWxH) 25.4 x 5.9 x 5.1cm

PROBE: 35.6cm long 6.4mm diameter metal flex probe

WEIGHT: 500 g

POWER: Three size "C" alkaline batteries

Part No	Description	Price	Qty	Total
TELS3000	ELECTRONIC LEAK DETECTOR	£262.00		
	TOTAL			
	DELIVERY			
	VAT@ 17.5%			
	Terms & Conditions Apply	TOTAL		

NO ORDERS WILL BE PROCESSED UNTIL:
 ALL PRICES ARE EXCLUDING
 DELIVERY & VAT@17.5%

1 DELIVERY COSTS ARE CONFIRMED.
2 CREDIT CARD SECURITY CODE
CONFIRMED BY TELEPHONE

Order by telephone, Fax, Post or e-mail.

Payment by

(1) **Cheque:** I enclose a cheque made payable to ACP Group

(2) **Credit Card:** Please charge my Visa ___ MasterCard ___ Amex ___ Switch ___ Issue No ___

ALL PRICES SUBJECT TO CHANGE

PRINTED APRIL 2005 E&OE

CARD NUMBER

--	--	--	--	--	--	--	--	--	--	--	--	--	--

EXPIRY DATE

--	--	--	--

CARD NAME _____
 COMPANY / HOME ADDRESS _____

POST CODE _____

SIGNED _____

DATE _____

TEL.NO (S) _____

FAX.NO _____

e-mail _____

SEND TO

ACP GROUP HOLLANDS BUSINESS CENTRE 21-27 HOLLANDS ROAD HAVERHILL CB9 8PU

www.acpg.co.uk

Fax 01440 708531

e-mail:sales@acpg.co.uk

Tel 01440 762211